BOTTOM HOLE ASSURANCE, INC.

No. DIR 43024ST-16

NDE Inspection Services

Email: BHAInc@bottomholeassurance.com
107 Citron Drive • Youngsville, LA 70592

Office: (337) 857-8994 Fax: (337) 857-8964
Bottomholeassurance.com

CUSTOMER HALLIBURTON ICC ☐ 3RD PARTY | FACILITY / LOCATION SERVICE TOOLS | AUTHORIZED BY JASON CLOSTIO | INVOICE NO.

RIG | PROJECT CHEVRON | P.O. / JOB # 909275080 | DATE: 4/30/2024

OCS-G & WELL

								PIN										BOX									
Serial #	Tool Description	Overall Length	Fishing Neck Length	Tong Space	Pin I.D.	Pin O.D.	Box O.D.	Connection Size	Pin Length	Pin Cylinder Diameter	Pin Nose Diameter	Pin Relief Diameter	Pin Rel. Width Pin Neck Lgth	Bevel Diameter	B S R	OK or Reject	Remarks	Connection Size	Counter Bore Length	Counter Bore Diameter	Bore Back Dia. Float Bore Dia.	Bore Back Lgth Float Bore Lgth	Box Thread Length	Counterbore Wall Thickness	Bevel Diameter	B S R	OK or Reject	Remarks
EQ# 14030981 EQ# 14030978	6.25" INT. SUB SURFACE X OVERSHOT INT. ASSY	12.42	11 5/16	7 7/16	3 1/4	6 5/8	6 5/8	5 1/4 CAS								Acc	CONN ONLY	NC 50	5/8	5 5/16					6 1/16		Acc	CONN. ONLY
EQ# 14030982 EQ# 13790102	6.25" INT. SUB SURFACE X OVERSHOT INT. ASSY	12.53	11 3/16	7 1/2	3 1/4	6 5/8	6 5/8	5 1/4 CAS								Acc	CONN ONLY	NC 50	5/8	5 5/16					6 1/16		Acc	CONN. ONLY
EQ# 13710170	8.15" INT. BALL VALVE ASSY	14.97	14 13/16	9 15/16	3	6 5/8	6 5/8	5 1/4 CAS								Acc	CONN ONLY	NC 50	5/8	5 5/16					6 1/16		Acc	CONN. ONLY
EQ# 14070354	9 5/8" RET. BRIDGE PLUG ASSY	11.52	13 3/16	16 13/16	3 1/4	6 5/8	6 5/8	NC 50	4 1/2				1/4	6 1/16		Acc	CONN ONLY	5 1/4 CAS									Acc	CONN. ONLY
EQ# 13483223	10 3/4" INT. PACKER ASSY	11.06	13 3/16	16 15/16	3	6 5/8	6 5/8	NC 50	4 1/2				1/4	6 1/16		Acc	CONN ONLY	5 1/4 CAS									Acc	CONN. ONLY
EQ# 14070352	9 5/8" INT. PACKER ASSY	11.52	13 3/16	16 15/16	3	6 5/8	6 5/8	NC 50	4 1/2				1/4	6 1/16		Acc	CONN ONLY	5 1/4 CAS									Acc	CONN. ONLY

Remarks: CONNECTION INSP AS PER MAN-GL-HAL-HCT-900 REV. 6.3 | Customer Rep Signoff:

Batch # Info.

20-B	23K007
Dry Powder	
7-HF	
White Contrast	
14-A	

Connection Inspection

Wet Flour. M.P.I.	☑	Dry M.P.I.	☐
Vis. Liq. Pen.	☐	Residual	☐
Flour Liq. Pen.	☐	Continuous	☑
Long. Insp.	☑	AC Current	☐
Trans. Insp.	☑	DC Current	☑

Body Inspection

Wet Flour. M.P.I.	☐	Residual	☐
Vis. Liq. Pen.	☐	Continuous	☐
Flour Liq. Pen.	☐	AC Current	☐
Long. Insp.	☐	DC Current	☐
Trans. Insp.	☐	Visible M.P.I.	☐

Body Dry M.P.I

Dry M.P.I.	☐	Residual	☐
Long. Insp.	☐	Continuous	☐
Trans. Insp.	☐	AC Current	☐
		DC Current	☐

System Effectiveness: LP-Comparitive Block ☐ Dry MP-Castrol Strip ☐ Wet MP-Castrol Strip ☑ Profile Gage RSC OK ☑

3rd Party Rep

Job Information

B BT | V BT | D | P BT

Signature:

Blacklight Inspection

Blacklight Intensity: 5689 | Bath Mixture: 0.25 | Whitelight: 0.1

Equipment / Inspector Information

Equipment Used From Unit # 23

Qual. Date(s) MT 4/26/2024 PT 4/26/2024

Level II Inspector: BRANSON THERIOT

Signature: Signature guarantees final walk thru of job and job site

Liquid Penetrant Inspection

Magnaflux Developer: SKD-S2

Batch #

Dwell Time: min

White Light:

Magnaflux Penetrant: ☐ SKL-WP2 (Check one) ☐ ZL-60D

Batch #

Dwell Time: min

By david.patin@bottomholeassurance.com at 3:38:15 PM, 4/30/2024